

SAFETY DATA SHEET

						SDS No: 0024
Section 1.	Pro	duct and Compai	ny Identificatio	n		
Product Name:	.005 A	dvantage Exterior S	Series			
Trade Name:	Impac	t Modified Acrylic				
Recommended L	Jse:	Signage, Other				
Restrictions on L	Jse:	None				
Manufacture:		Innovative Plastics In 5409 Hamlet Drive Findlay, OH 45840	IC.	In Case of Emergency: Information:	Call: Email: Call: Email:	Medical:911 Poison Control: 800-589-3897 1-815-477-0778
Section 2.	Haza	rd Identification			Liiidii.	info@inoplas.com
GHS Classificatio		Not Classified				NEW GHS Hazard Categories
GHS Label Eleme	ents:	Not Applicable				Category 1 = Severe Hazard
						Category 2 = Serious Hazard
GHS Rating		_				Category 3 = Moderate Hazard
Health	5					Category 4 = Slight Hazard
Flammability	4					Category 5 = Minimal Hazard
Instability	5					
Special						
Other Hazards:		Not Applicable				
Section 3.	Com	position / Inform	ation on Ingre	dients		
Name			CAS #	% by Weight		OHSA
Р (EA/MM	A)	Proprietary	50-54		Ν
Acrylic St	yrene Co	opolymer	Proprietary	35-50		Ν
Methy	l metha	crylate	80-62-6	< 0.5		Y
Eth	iyl acryla	ate	140-88-5	< 0.1		Y
		d with a "Y" in the OS mmunication Standa		enfitied as hazardous chemic 200).	als accord	ing to the criteria of
				OSHA regulations, this SDS c SDS should be retained and		aluable information for employees and other users of this
The components	s of this	product are all on the	e TSCA Inventory li	ist.		
				unts below reportable limits.		

Section 4.	ction 4. First Aid Measures			
Inhalation:	Dust and process	vapors may be irritation to the nose, throat and respiratory tract. Remove to fresh air. If not		
	breathing, give artificial respiration. If breathing is difficult, give oxygen. Get Medical attention.			
Eyes:	Dust, fines and process vapors may irritate the eyes. Immediately flush eyes with water for at least 15 minutes. Get			
Lyes.	medical attention.			
Skin:	Exposure to molten plastic may cause thermal burns. If molten material comes in contact with the skin, cool under ice			
	water or a running stream.			
Ingestion:	No adverse health effects expected from ingestion.			
Section 5.	tion 5. Fire-Fighting Measures			
		Dry Chemical, Water Spray, Foam Carbon Dioxide. Avoid using direct streams of water on		
Suitable Extinguishing Methods:		molten burning material.		

Carbon monoxide, carbon dioxide, original monome Wear self-contained breathing apparatus and protect se Measures See Section 8 - Exposure Controls / Personal Protect No Special environmental precautions required. Iment and Cleaning Up f this material should not be necessary. Sweep up or isposal. rage m heat, flame and strong oxidizing agents. m heat, sparks, and flame. Store in cool place in origin and Personal Protection Inhalation of vapors may result in irritation of upper US. ACGIF Threshold	ctive suit. ion. gather material and place in appropriate nal container and protect form sunlight.
See Measures See Section 8 - Exposure Controls / Personal Protect No Special environmental precautions required. Iment and Cleaning Up f this material should not be necessary. Sweep up or isposal. rage n heat, flame and strong oxidizing agents. n heat, sparks, and flame. Store in cool place in origin and Personal Protection Inhalation of vapors may result in irritation of upper US. ACGIF Threshole	ion. gather material and place in appropriate nal container and protect form sunlight.
See Section 8 - Exposure Controls / Personal Protect No Special environmental precautions required. ment and Cleaning Up f this material should not be necessary. Sweep up or isposal. rage m heat, flame and strong oxidizing agents. m heat, sparks, and flame. Store in cool place in origin and Personal Protection Inhalation of vapors may result in irritation of upper US. ACGIF Threshole	gather material and place in appropriate nal container and protect form sunlight.
No Special environmental precautions required. ment and Cleaning Up f this material should not be necessary. Sweep up or isposal. rage m heat, flame and strong oxidizing agents. m heat, sparks, and flame. Store in cool place in origin and Personal Protection Inhalation of vapors may result in irritation of upper US. ACGIF Threshold	gather material and place in appropriate nal container and protect form sunlight.
ment and Cleaning Up f this material should not be necessary. Sweep up or isposal. rage m heat, flame and strong oxidizing agents. m heat, sparks, and flame. Store in cool place in origin and Personal Protection Inhalation of vapors may result in irritation of upper US. ACGIF Threshold	nal container and protect form sunlight.
f this material should not be necessary. Sweep up or isposal. rage m heat, flame and strong oxidizing agents. m heat, sparks, and flame. Store in cool place in origin and Personal Protection Inhalation of vapors may result in irritation of upper US. ACGIF Threshold	nal container and protect form sunlight.
isposal. rage m heat, flame and strong oxidizing agents. m heat, sparks, and flame. Store in cool place in origin and Personal Protection Inhalation of vapors may result in irritation of upper US. ACGIF Threshold	nal container and protect form sunlight.
rage m heat, flame and strong oxidizing agents. m heat, sparks, and flame. Store in cool place in origin and Personal Protection Inhalation of vapors may result in irritation of upper US. ACGIF Threshole	
n heat, flame and strong oxidizing agents. n heat, sparks, and flame. Store in cool place in origin and Personal Protection Inhalation of vapors may result in irritation of upper US. ACGIF Threshole	
m heat, sparks, and flame. Store in cool place in origin and Personal Protection Inhalation of vapors may result in irritation of upper US. ACGIF Threshole	
and Personal Protection Inhalation of vapors may result in irritation of upper US. ACGIF Threshold	
Inhalation of vapors may result in irritation of upper US. ACGIF Threshole	respiratory tract
US. ACGIF Threshold	respiratory tract
US. ACGIF Threshold	respiratory tract
_	d Limit Values
Form:	Inhalable particles
Time weighted average	10 mg/m3
Form:	Respirable particles
	3 mg/m3
-	Respirable fraction
PEL:	5 mg/m3
Form:	Total dust
	15 mg/m3
US. OSHA Table Z-3 (29	
Form:	Respirable fraction
Time weighted average	15 ppm
Form:	Total dust
Time weighted average	50 ppm
Form:	Respirable fraction
	5 mg/m3
Form:	Total dust
Time weighted average	15 mg/m3
for here all the surrouting the state of the state	
	ire.
points of tume generation or if dusty conditions prevai	l.
	ntact.
ves and protective clothing to prevent skin contact.	
t /	Form: Time weighted average Form: Time weighted average US. OSHA Table Z-1 Limits for Air Cor Form: PEL: US. OSHA Table Z-3 (25) Form: Time weighted average Form: Time weighted average Form: Time weighted average Form: Time weighted average Form:

Appearance:	Various Colors	Vapor Pressure:	Not Applicable
Odor:	Slightly acrylic	Vapor Density:	Not Applicable
pH:	Not applicable	Relative Density:	1.19 g/cm3
Melting Point / Freezing Point:	No data available	Solubility (ies):	Not Applicable
Boiling Point:	No data available	Partition Coefficient (N-Octanol/Water):	No data available
Flash Point:	Not applicable	Auto-Ignition Temperature:	739°F (393°C)
Evaporation Rate:	Not applicable	Decomposition Temperature:	>572°F (> 300°C)
Flammability (solid, gas):	See GHS in section 2	Viscosity:	No data available
Upper Explosive Limit:	Not applicable	Specific Gravity:	1.19 Water = 1 (liquid)
Lower Explosive Limit:	Not applicable	Percent Volatile:	0%

Section 10. Stability Reactivity					
No data available					
Stable					
Hazardous polymerization does not occur					
Avoid flames, welding arcs, potential ignition sources, or other high temperature sources,					
prolonged contact with acids, alkalis and strong oxidizing agents					
None under normal conditions of use					
Carbon oxides, Acrylates, Methacrylates, Hazardous organic compounds					
No data available					

Section 11. Toxicological Information

Irritation	Effects
minuation	LIICULS

Eye Irritation:	Solid particles may cause transient irritation from mechanical abrasion.				
Skin Irritation:	Not expected to cause skin irritation. Molten material may cause thermal burns.				
Inhalation:	Not a likely route of exposure. Process fumes may cause irritation.				
Ingestion:	May cause a choking hazard if swallowed.				

Data for PLEXIGLAS® DR®-101 ACRYLIC RESIN

Acute Toxicity

Dermal:	Acute toxicity estimate > 5,000 mg/kg
Inhalation:	4 h Acute toxicity estimate > 10 mg/L

Data for Acrylic copolymers (Proprietary)

Other Information

The information presented is from representative materials in this chemical class. The results may vary depending on the test substance.

Effects due to processing releases or residual monomer: Possible cross sensitization with other acrylates and methacrylates.

Data for Acrylic styrene copolymers (proprietary)

Other Information

The information presented is from a representative material with a similar structure. The results vary depending on the size and composition of the test substance.

Effects due to processing releases or residual monomer: Possible cross sensitization with other acrylates and methacrylates.

Additional Toxicological Information

When used and handled according to specifications, the product does not have any harmful effects according to research and information provided by suppliers.

Carcinogenic Effect

International Agency for Research on Cancer (IARC) : Group3 NOT classifiable as to its carcinogenicity to humans.

Section 12. Ecological Information			
Eco-toxicity:	Toxicity to fish - No relevant studies identified.		
Persistence and Degradability:	This material is not expected to be readily biodegradable.		
Bio-accumulate Potential:	Product is not likely to accumulate in biological organisms.		

This Product has not been found to migrate through soils.

Other Adverse Effects:

This Substance is not in Annex I of Regulation (EC) 2037/2000 on substances that deplete the

ozone layer.

Section 13. Disposal Considerations

Disposal Methods

Product Recommendation:

1. Recycle (Reprocess) if product has not been contaminated so as to make it unsuitable for its intended use.

2. Disposal through controlled incineration or authorized waste dump in accordance with Local, State or Federal Regulations.

Uncleaned Packaging Recommendation:

1. Disposal must be done in accordance with Local, State, or Federal Regulation.

Section 14. Transportation	on Information		
UN Number:	Not Relevant		
UN Proper Shipping Name:	Not Relevant		
Transportation Hazard Class(es)			
DOT:	Not Regulated/classified		
ADR / RID:	Not Regulated/classified		
IMDG:	Not Regulated/classified		
ICAO/IATA	Not Regulated/classified		
Packing Group:	Not Applicable		
Environmental Hazards:	Not Relevant		
Transportation in Bulk (According	to Annex II of MARPOL 73/78 and IBC Code):	Not Relevant	
Special Precautions for User:	No special precautions		

Section 15. Regulatory Information

(Not meant to be all-inclusive -- selected regulations represented)

Hazard categories under criteria of SARA Title III Rules (40 CFR Part 370)

Immediate (Acute) Health	N	Delayed (Chronic) Health	Ν
Sudden Release of Pressure	N	Reactive	Ν
Fire	N		

The components of this product are all on the TSCA inventory list.

INGREDIENT RELATED REGULATORY INFORMATION:

SARA REPORTABLE QUANTITIES	CERCLA RQ	SARA TPQ
Ethyl acrylate	1000 LBS	N/A
Methyl methacrylate	1000 LBS	N/A
P (EA/MMA)	N/A	N/A

SARA TITLE III, SECTION 313

This product does contain chemical(s), which are defined as toxic chemicals under and subject to the reporting requirements of, Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. See section 2.

Chemical Name	CAS-No.		De minimis concentration		Reportable Threshold:
Ethyl acrylate	Not assigned	ed	Not assigned		Not assigned
Methy methacrylate	Not assigned	ed	Not assigned		Not assigned
2-Propenoic acid, ethyl ester	140-88-5		0.10%		10000 lbs (otherwise used (non- manufacturing/processing)) 25000 lbs (manufacturing and processing)
Comprehensive Environmental Res	ponse, Compen	sation, and Lia	ability Act (CERCLA)-Reporta	able Qua	ntity (RQ)
Chemical Name		CAS-No.		Reportable quantity	
2-Propenoic acid, 2-methyl-, methyl ester 80		80-62-6		1000 lbs	

2-Propenoic acid, ethyl ester		140-88-5	1000 lbs
Chemical Inventory Status			
EU. EINECS		EINECS	Conforms to
United States TSCA Inventory		TSCA	The components of this product are all on the TSCA Inventory
Canadian Domestic Substnaces List (DSL)		DSL	All components of this product are on the Canadian DSL.
China. Inventory of Existing Chemical Substances in China (IECSC)		IECSC (CN)	Does not conform
Japan. ENCS - Existing and New Chemical Substances Inventory		ENCS (JP)	Does not conform
Japan. ISHL-Inventory of Chemical Substances		ISHL (JP)	Does not conform
Korea. Korean Existing Chemicals Inventory		KECI (KR)	Conforms to
Philippines Inventory of Chemicals and Chemical Substances (PICCS)		PICCS (PH)	Conforms to
Australia Inventory of Chemical Substances		AICS	Conforms to
OSHA HazCom: This Material	is not Hazar	dous b OSHA Hazardous Comn	nunication Standard 29 CFR 1910.1200
SARA 313:			
Immediate Hazard: NO	Fire Haza	ard: NO	Reactivity Hazard: NO
Delayed Hazard: NO	azard: NO Pressure Hazard: NO		

No Additional Information

NOTICE: The information presented in this Safety Data Sheet is based on data considered to be accurate as of the date this Safety Data Sheet was prepared. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In additional, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Revision Date: September 2023